

METHOD AND DEVICE FOR GENERATING A PERSON'S PORTRAIT,  
METHOD AND DEVICE FOR COMMUNICATIONS, AND  
COMPUTER PRODUCT

5 FIELD OF THE INVENTION

Sub 7  
A1 The present invention relates to a technology for  
generating an image of a person's portrait in which, from  
a two-dimensional image containing a person's face picked  
up by an image sensor, the feature of the subject person  
10 is emphasized to generate the person's portrait or generate  
a deformed image of the person's portrait. This invention  
also relates to method and device for communication, and  
a computer readable recording medium which stores a computer  
program which when executed on a computer realizes the  
15 methods according to the present invention.

BACKGROUND OF THE INVENTION

Sub 7  
A2 In recent years, it has become possible to send/receive  
electronic mails not only on a personal computer but also  
20 on a portable terminal. Furthermore, not only documents,  
but also sender's portrait have been widely attached to the  
electronic mails. When creating such a portrait by using  
a conventional method, it is necessary for the user to  
manually make selections from prepared parts of several tens  
25 or more kinds, such as face outline parts, face parts and

hairstyles, and combine them all together. In this case,  
a large number of combinations are available, and as a result,  
a great amount of workload is imposed on the user in an attempt  
to create a desired person's portrait. For this reason,  
5 there has been a strong demand for a device which can easily  
and automatically generate a person's portrait using an image  
of that person acquired by a camera. In order to create  
a person's portrait, such a device needs to automatically  
carry out a sequence of processes of extracting the face  
10 portion from the image, detecting eyes, mouth, etc., and  
replacing the desired parts with already prepared desired  
templates.

As one example of the related technique, Japanese  
Laid-Open Patent Application No. 255017/1998 (Tokukaihei  
15 10-255017) discloses a method and device for generating a  
person's portrait. In this method, with respect to the face  
area detection, (R, G, B) values of skin color are  
preliminarily set to a specified range, and pixels having  
the corresponding color are marked, and clustered so as to  
20 carry out the detection, while the face parts detection is  
carried out by template matching processes. However, with  
respect to the face area detection,

Sub  
A<sub>2</sub> (1) the face color is influenced by illumination conditions,  
resulting in a difficulty in detecting the face area; in  
25 some cases;

(2) the face color is not located within the above-mentioned range of the (R, G, B) values due to differences in human races, etc.; and

(3) when pixels having a color similar to the face color exists on the background, it is sometimes difficult to detect the face area.

Moreover, with respect to the face parts position detection, conventional problems are that,

(4) when the number of face-part templates is increased so as to match various face parts contained in an image, the amount of calculations increases due to increased collation processes, resulting in degradation in the execution speed; and

(5) a dark shadow tends to appear on the periphery of a face part in an image depending on illumination conditions, resulting in a difficulty in the template matching.

#### SUMMARY OF THE INVENTION

It is an object of this invention to provide a person's portrait generation device which picks up a two-dimensional image that contains the person's face by using an image sensor, analyzes characteristics features in the face from the picked image, and automatically generates an image in which characteristics features of the face are emphasized. It is another object of this invention to provide a person's

portrait generation method for such a device. It is still another object of this invention to provide a communication terminal which incorporates the person's portrait generation device according to this invention, and provide  
5 a communication method thereof. It is still another object of this invention a computer readable recording medium which stores a computer program which when executed on a computer realizes the methods according to the present invention.

According to one aspect of this invention,  
10 two-dimensional images containing a person's face are picked, area corresponding to head of the person is extracted based on a differential image of the acquired two-dimensional images. After that, position of characteristic features of the face of that person are detected from the area  
15 corresponding to head of the person. Then, outline of the face is detected by detecting a border between the face and the background of the image. Finally, the person's portrait in which the characteristics features of the person's face are emphasized is generated based upon the acquired  
20 two-dimensional images and data corresponding to the area corresponding to head, position of characteristic features of the face, and the outline of the face.

According to another aspect of this invention, a two-dimensional image containing a person's face is picked,  
25 area corresponding to head of the person is extracted from

the acquired two-dimensional image. After that, position of characteristic features of the face of that person are detected by dividing the head area thus extracted into face part areas for respective face parts and finding projection data of binarized images for the respective face parts areas. Then, outline of the face is detected by detecting a border between the face and the background of the image. Finally, the person's portrait in which the characteristics features of the person's face are emphasized is generated based upon the acquired two-dimensional image and data corresponding to the area corresponding to head, position of characteristic features of the face, and the outline of the face.

According to still another aspect of this invention, a two-dimensional image containing a person's face is picked, and area corresponding to head of the person is extracted from the acquired two-dimensional image. After that, position of characteristic features of the face of that person are detected from the area corresponding to head of the person. Then, outline of the face is detected by detecting a border between the face and the background of the image. Finally, the person's portrait in which the characteristics features of the person's face are emphasized is generated based upon the acquired two-dimensional image and data corresponding to the area corresponding to head, position of characteristic features of the face, and the

outline of the face.

According to still another aspect of this invention, a two-dimensional image containing a person's face is picked, and area corresponding to head of the person is extracted  
5 from the acquired two-dimensional image. After that, position of characteristic features of the face for each of the face parts of that person are detected from the area corresponding to head of the person. Then, outline of the face is detected by detecting a border between the face and  
10 the background of the image. Finally, the person's portrait in which the characteristics features of the person's face are emphasized by changing the two-dimensional image with respect to each of the face parts.

Furthermore, a communication method and device  
15 according to still another aspect of this invention is capable of electronically transmitting or receiving the generated portrait using a communication unit. The communication device is, for, example, a cellular telephone or a PDA.

20 Furthermore, a computer readable recording medium according to still another aspect of the present invention stores a computer program which when executed realizes the methods according to the present invention.

Other objects and features of this invention will  
25 become apparent from the following description with

reference to the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram that shows an arrangement  
5 of a person's portrait generation device in accordance with  
the first embodiment of the present invention.

Fig. 2 is an explanatory drawing that shows the  
operation of a head area extracting section in accordance  
with the first embodiment of the present invention.

10 Fig. 3 is an explanatory drawing that shows a median  
filter in accordance with the first embodiment of the present  
invention.

Fig. 4 is an explanatory drawing that shows a smoothing  
filter in accordance with the first embodiment of the present  
15 invention.

Fig. 5 is an explanatory drawing that shows the  
operation of a feature detection section in accordance with  
the first embodiment of the present invention.

Fig. 6 is an explanatory drawing that shows the  
20 operation of a face outline determining section in accordance  
with the first embodiment of the present invention.

Fig. 7 is a drawing that shows a specific example for  
a face portrait image that is formed based upon an input  
image by an image processing section in accordance with the  
25 first embodiment of the present invention.

Fig. 8 is a flow chart indicating the steps in a person's portrait generation method in accordance with the first embodiment of the present invention.

Fig. 9 is a flow chart indicating an image input step  
5 in accordance with the first embodiment of the present invention.

Fig. 10 is a flow chart indicating a head area extracting step in accordance with the first embodiment of the present invention.

10 Fig. 11 is a flow chart indicating a feature extracting step in accordance with the first embodiment of the present invention.

Fig. 12 is a flow chart indicating a face outline determining step in accordance with the first embodiment  
15 of the present invention.

Fig. 13 is a flow chart indicating an image processing step in accordance with the first embodiment of the present invention.

Fig. 14 is an explanatory drawing that shows a specific  
20 example for a face portrait image that is formed based upon an input image by an image processing section and a deforming method from the original image, in accordance with the second embodiment of the present invention.

Fig. 15 is an explanatory drawing that shows a specific  
25 example for a face portrait image that is formed based upon



an input image by an image processing section and a deforming method from the original image, in accordance with the third embodiment of the present invention.

Fig. 16 is an explanatory drawing that shows a communication terminal and a communication method in accordance with the fourth embodiment of the present invention.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

A first embodiment of the present invention will be explained first with reference to the accompanying drawings. Fig. 1 is a block diagram that shows a construction of an image generation device in accordance with the first embodiment of the present invention. This device comprises five sections. That is, an image input section 1, a head area extracting section 2, a feature detection section 3, a face outline determining section 4 and an image processing section 5.

For convenience of explanation, it will be assumed here that only one person is present in an image that has been picked up by an image sensor, and that although there is change in the position of the person there is no movement in the background of the image.

The image input section 1 including an image sensor picks up two-dimensional images. The head area extracting

section 2 analyzes a plurality of the two-dimensional images picked up by the image input section 1 so that an area including the head of a person is extracted. The feature detection section 3 analyzes the luminance values of the input images with respect to the area extracted by the head area extracting section 2 so that the positions of face parts such as the eyes and mouth are detected. Based upon the face parts positions detected by the feature detection section 3, the face outline determining section 4 analyzes the color of a specific target area, such as the face color of the person, and based upon this analysis, determines the border between the target area and the background. Based upon output information from the head area extracting section 2, the feature detection section 3 and the face outline determining section 4, the image processing section 5 creates an image in which the characteristic features of the target area is emphasized from the input images.

Referring to Fig. 2A to Fig. 2K, a detailed explanation will be given of the operation of the head area extracting section 2. In the first embodiment of the present invention, the head area extracting section 2 calculates a differential image by using two images that have time-wise differences among the input images picked up by the image input section. In this case, in general, it is preferable to use two images that virtually continue in terms of time. Moreover, in the

differential image, pixel data are constituted by values obtained by binarizing the absolute value of a difference between corresponding pixel values.

Fig. 2A to Fig. 2K are explanatory draws that show  
5 how the head area of a person is detected by using the differential image calculated from the images picked up by the image input section 1. Fig. 2A shows an image including the head of a person picked up by the image input section 1. Fig. 2B is a differential image that has been binarized.  
10 In other words, a black pixel indicates a pixel in which there is any change in the pixel value, that is, a pixel that has been moved. In this example, only one person moves; however, black pixels are sparsely mixed into the background due to noise contained in the image. Moreover, when any  
15 moving object is contained in the background, black pixels are also mixed into the background portion; however, these black pixels are processed as noise when the main portion of the image is occupied by one person.

Next, from Fig. 2B, black pixels are retrieved in the  
20 horizontal direction of the image. In other words, with respect to black pixels that are aligned along one horizontal line, the position of a black pixel is retrieved rightwards from the left end, or leftwards from the right end, and the position of the black pixel that has been first encountered  
25 is recorded. This process is repeated with respect to all

the horizontal lines. Fig. 2C shows the results (hereinafter, referred to as left side profile) of the retrieval rightwards from the left end in which the positions of the black pixels that have been first encountered are connected from the upper end to the lower end. Fig. 2D shows the results (hereinafter, referred to as right side profile) of the retrieval leftwards from the right end obtained in the same manner with respect to the positions of the black pixels.

As can be seen in these cases, each of the two profiles has an irregular edge shape due to the black pixels that are noise components sparsely contained in the background. Therefore, prior to obtaining the outline of the head area, it is necessary to eliminate the irregular edge shape that forms noise components.

In order to eliminate this irregular shape, a filtering process is preferably carried out. For example, a median filter in which the horizontal position in the right and left profile is represented as a length value from the end is applied so as to eliminate the noise components.

Referring to Fig. 3, a brief explanation will be given of the median filter (center value filter).

In the median filter, in general,  $n$ -number of data  $d[0], \dots, d[n-1]$  are sorted in the order to sizes, and  $d[k]$  ( $0 \leq k \leq n-1$ ), which is located in the middle in

the order to sizes, is selected as an output value.

In Fig. 3, for example, with respect to N-number of column data  $d(1)$  to  $d(N)$ , with respect to arbitrary data  $d(k)$ , a total of  $(2m + 1)$  number of data including m-number of proximity data before and after thereof are sorted in the order to sizes, and  $d(k)$  is replaced by a value located in just the middle number  $(m + 1)$ ; thus, the filtering process is realized. In this manner, the slope of data (contrast) is properly maintained. In other words, as shown in Fig. 3, when high values are continuously inputted as in the case of an (x) data group (from the fifth data to the tenth data from the top) before the application of the process, the contrast (gaps between the values) is appropriately maintained as shown in the Figure indicating a state after the application of the process.

In contrast, even when a high value is singly inputted as in the case of a (y) data group (from the fifth data from the bottom to the third data from the bottom) before the application of the process, this is eliminated by taking the center value of the proximity data as shown in the Figure indicating a state after the application of the process, thereby making it possible to eliminate the noise.

Fig. 2E and Fig. 2F respectively show the results obtained by applying the median filter to the profiles of Fig. 2C and Fig. 2D. However, as shown by the results of

Fig. 2E and Fig. 2F, even the application of the median filter sometimes can not eliminate all the noise components depending on the degree of noise mixture. Therefore, the application of a smoothing filter to Fig. 2E and Fig. 2F  
5 makes it possible to further eliminate the noise components.

In the smoothing filter, in general, supposing that n-number of data  $d[0], \dots, d[n-1]$  exist, for example, with respect to arbitrary profile data  $d[k]$ ,  $(d[k-1] + d[k] + d[k+1])/3$  is calculated, and the average value is  
10 outputted as  $d[k]$ .

Referring to Fig. 4, a brief explanation will be given of the smoothing filter.

In Fig. 4, for example, in connection with N-number of column data  $d(1)$  to  $d(N)$ , with respect to arbitrary  
15 data  $d(k)$ , an average value of a total of  $(2m+1)$  number of data including m-number of proximity data before and after thereof are calculated to find an average value, and  $d(k)$  is replaced by this value; thus, the filtering process is realized. In this manner, the data can be smoothed by using  
20 comparatively less amount of calculations. In other words, as shown in Fig. 4, when high values are continuously inputted as in the case of an (x) data group (from the fifth data to the tenth data from the top) before the application of the process, a smoothing process is available as a whole  
25 although the contrast becomes slightly dull as shown in the

Figure indicating a state after the application of the process.

Moreover, even when a high value is singly inputted as in the case of a (y) data group (from the fifth data from the bottom to the third data from the bottom) before the application of the process, noise is clearly eliminated as shown in the Figure indicating a state after the application of the process.

Fig. 2G and Fig. 2H show the results of smoothing processes carried out on the right and left profiles of Fig. 2E and Fig. 2F. These show that noise components are virtually eliminated so that the right and left outlines of the head are obtained.

Next, an explanation will be given of a method in which a rectangular area enclosing the head area (hereinafter, referred to as a head rectangular shape) is determined by utilizing the right and left profiles shown in Fig. 2G and Fig. 2H.

Fig. 2I shows a state in which left side profile 6 of Fig. 2G and right side profile 7 of Fig. 2H are superposed. Here, in Fig. 2I, retrieval is carried out downward, starting from the upper end of the horizontal line, with respect to the right and left profiles so as to find the first crossing portion, and a horizontal line passing through the first crossing portion is defined as the upper side of the head

rectangular shape 8. Next, in order to determine the left side of the head rectangular shape 8, the retrieval is further continued downward with respect to the left side profile 6. A pixel position at which the distance from the right end of the image first starts to decrease is recorded, and a vertical line passing through this point is defined as the left side of the head rectangular shape 8, and recorded. With respect to the right side profile 7, the retrieval is made in the same manner so that a vertical line passing through the resulting pixel position is defined as the right side of the head rectangular shape 8, and recorded.

With respect to the remaining lower side of the head rectangular shape 8, a candidate position is determined by utilizing the fact that the ratio of the width and the height of the head rectangular shape 8 of a general person is virtually constant. More specifically, supposing that the width is  $W$ , the height is  $H$  and the constant representing the average ratio is  $k$ ,  $H/W = k$  is obtained. Here, the value of  $W$  is given by the distances of the right side and left side of the head rectangular shape 8 that have already been determined, and the position (the distance from the upper end of the image)  $p$  of the upper side has already been determined; therefore, supposing that the candidate position of the lower side to be found is  $p'$ ,  $p'$  (the distance from the upper end of the image) is calculated by the following



expression:

$$p' = k \times W + p.$$

Fig. 2J shows a state in which the head rectangular shape 8 thus determined from the right and left profiles is displayed in a superposed manner. Finally, the head rectangular shape 8 is determined as a silhouette of a person to which movements of the person are reflected as shown in Fig. 2K that is obtained in a manner so as to enclose the head.

Next, an explanation will be given of the operation of the feature detection section 3. Fig. 5A to Fig. 5E is a drawing that explains an example in which luminance values of an input image within the head rectangular shape 8 are analyzed so that the positions of characteristic features of the eyes, nose, mouth, etc. are specified.

Fig. 5A shows an example of an input image. Fig. 5B shows a state in which the head rectangular shape 8 extracted by the head area extracting section 2 is displayed in a superposed manner. Fig. 5C shows areas 9 to 17 used for specifying rectangular areas that are analyzing ranges for identifying the positions of respective face parts that form characteristic features, and these areas are obtained by preliminarily finding relative positions of the respective face parts with respect to the head shape of a general person.

In other words, with respect to the upper, lower, right

and left sides of each of the rectangular shape areas, the right eye is specified by points 14, 15, 10 and 9, the right eye is specified by points 14, 15, 9 and 13, the nose is specified by 15, 16, 11 and 12, and the mouth is specified  
5 by 16, 17, 11 and 12.

Next, among the face parts detections by the use of Fig. 5D, for example, an explanation will be given of a method by which the position of the right eye is detected. The detection area surrounded by 14, 15, 9 and 10 is obtained  
10 by binarizing pixel values of the input image, and with respect to the pixel values, values greater than a threshold value are represented by 0 (white pixels) and values other than this case are represented by 1 (black pixels). In order to calculate the detection position (the center of the pupil)  
15 of the right eye by using the center-of-gravity position, projection data are obtained by adding values of respective pixels in the binarized image within the detection area for each row and each column, and the center-of-gravity position of each of these is calculated so that the horizontal position  
20 and vertical position of the right eye detection position are obtained. In these cases, 25 and 26 respectively represent projection data in the vertical direction (for each column) and projection data in the horizontal direction (for each row). The center-of-gravity positions are  
25 calculated from these projection data. In the horizontal

direction, 27 is obtained as the center-of-gravity position, and in the vertical direction, 28 is obtained as such, with the result that the right-eye detection position 19 shown in Fig. 5E is obtained.

5           Here, with respect to the horizontal and vertical positions, the positions, each providing the maximum value of the projection data, may be used instead of the center-of-gravity of the projection data so as to calculate these positions.

10           In the same manner, the detection position 18, 20 or 21 shown in Fig. 5E for each of the left eye, nose and mouth is found by calculating the center of gravity from the binarized image within each of the rectangular shape areas.

          The above explanation has been given of the eyes, nose  
15   and mouth serving as the characteristic features; however, in an attempt to improve the precision as a person's portrait, the detecting process may be carried out on other parts elements, such as the eyebrows, front hairstyle, cheeks and ears.

20           Next, referring to Fig. 6A to Fig. 6G, an explanation will be given of the operation of the face outline determining section 4. In the present embodiment, the face outline determining section 4 calculates the RGB value of the average color of pixels in the proximity of each face parts position  
25   by using information of the face parts position detected

by the head feature detection section 3 based upon the input image of the image input section 1, and converts this value to a value on the HSV color system; thus, the RGB values of all the pixels of the input image are converted to the HSV values, and these values are plotted on the HSV color system. At this time, an area centered on the HSV value of the average color is set on the HSV color system map, and the pixel data located within the area is again returned to the RGB color system, and plotted on the original input image. Based upon the results of these processes, the face area is estimated.

In this case, with respect to the conversion of the color system from the RGB values to the HSV values, for example, a method disclosed in US. Patent No. 5586197 is used so as to realize the conversion. Here, the RGB color system uses a cubic shape having R, G, B as its axes, while the HSV color system uses a cylinder shape as shown in Fig. 6A. With respect to the HSV values, the value V (luminance) is represented by the height from the bottom of the cylinder serving as the reference as shown in Fig. 1A, the value S (the degree of saturation, the density of color) is represented by the distance from the center axis C of the cylinder as shown in Fig. 6B, and H (the degree of chrominance, the kind of color) is represented by an angle from a line CR of a mapped red color with the values of G and B of the

RGB values being set to 0 on a disc that is a cross-section of the cylinder.

Fig. 6C shows an example in which upon conversion of the RGB values of an input image into HSV values, these values  
5 are plotted on the disc shown in Fig. 6B with differences in the value of V being ignored.

Next, an explanation will be given of a system in which an area is provided on the HSV color system based upon the average color in the vicinity of the face parts position  
10 and the face area is specified based upon the color within the area. Fig. 6D and Fig. 6E show color judgment areas for extracting the face area, and 22 represents a position obtained when the average color (RGB value) in the vicinity of the face parts position is converted into an HSV value.  
15 As shown in Fig. 6D, the shape of the color judgment area may be set as an elliptical shape area 23 with a line CX serving as a major axis, when a crossing point of the circumference and the extended line of the line connecting the average color position 22 and the center C is set as  
20 X, or as shown in Fig. 6E, a delta shape area 24 may be set. In either of the cases, pixels within the area including the average color position 22 and having colors similar to this can be specified as face area candidates.

An explanation will be given of a system in which,  
25 by analyzing the positions of the pixels serving as face

area candidates that have been determined as described above, the face outline, especially, the border line in the vicinity of the jaw, is estimated. The determining process of the face outline in the vicinity of the jaw is important in creating a person's portrait. In other words, the case in which the right and left smoothed profiles 6 and 7 are simply used as the face outline in the vicinity of the jaw fails to provide a person's portrait sufficiently representing the characteristic features of the face, and in order to obtain a superior person's portrait, it is necessary to individually determine the face outlines in the vicinity of the jaw.

First, with respect to a head outline 29 shown in Fig. 6F, the inside of the head rectangular shape 8 is analyzed by the above-mentioned specifying method of the face area by using the differential image used in the area extracting section 2, partial elliptical shapes of four corners are calculated and set in a manner so as to surround this specified face portion, and one portion of each of the right and left sides of the head rectangular shape 8 is further added to the partial elliptical shape so that the outline of the face including a jaw border line 30 is formed.

More specifically, on the lower side surrounded by the right and left side of the head rectangular shape 8, that is, within the semi-elliptical area of the head outline

29, the rate of the face area candidate pixels, explained before, is calculated. In this case, the semi-elliptical shapes of the head outline 29 are contracted toward the respective centers at the same curvature until the calculated  
5 rate has exceeded a predetermined threshold value, thereby determining the jaw border line 30. Fig. 6G shows an example of the estimated results of the jaw border line 30 obtained by applying the above-mentioned technique to an actual image.

Lastly, an explanation will be given of the operation  
10 of the image processing section 5. In the first embodiment, the image processing section 5 generates a person's portrait of a face image contained in an original image by using the head rectangular shape 8 detected by the head area extracting section 2, the positions of the eyes 18, 19 and the mouth  
15 position 21 detected by the feature detection section 3, the head outline 29 detected by the face outline determining section 4 and the estimated jaw border line 30. Fig. 7 shows an example of a person's portrait image generated by the image processing section 5. In this image, the upper half  
20 of the head outline 29 and the portion surrounded by the jaw border line 30 thereof are extracted from the input image to form a face image, and after having been subjected to an edge-emphasizing process, this is binarized to form a line image. At this time, the inside of the face area may  
25 be painted using the average color to which the face color

calculated by the face outline determining section 4 is reflected; thus, it is possible to obtain the person's portrait image as a color image.

The above-mentioned description has discussed the construction of the person's portrait generation device, and the following description will briefly discuss the person's portrait generation method by reference to a flow chart that summarizes its sequences of processes.

Fig. 8 is a flow chart that shows the person's portrait generation method of the present invention corresponding to Fig. 1. Steps 101 to 105 shown in this diagram are performed respectively by the sections 1 to 5 shown in Fig. 1. It is to be noted that the sequence of steps 103 and 104 may be reversed.

Fig. 9 to Fig. 12 are flow charts showing detail processing in the steps 101 to 104 shown in Fig. 8.

In the image input step 101 shown in Fig. 9, first, two image buffers in which input images are stored are initialized. Next, image input is started. Then, image data are respectively stored in the two image buffers, and if no other pickup image exists, the image pickup process is completed, and the image data are outputted.

In a head area extracting step 102 shown in Fig. 10, first, based upon the image data outputted from the two image buffers, calculations are made to generate a differential



image between binarized frames. Next, the differential image between the binarized frames is analyzed to extract a head rectangular shape.

In a feature detection step 103 shown in Fig. 11, first,  
5 based upon the rectangular area extracted by the head area extracting step 102 and relative positions of the respective face parts with respect to the head shape that have been preliminarily provided, an analyzing range used for detecting a position of each of the face parts is determined.  
10 Next, the image within the analyzing range is analyzed for each of the face parts so that the center position of each of the face parts is detected.

In the face outline determining step 104 shown in Fig. 12, first, based upon the image inputted from the image input  
15 step 101, the average color of the face is calculated by using RGB pixel data in the vicinity of each of the face part positions detected by the feature detection step 103. Then, within the rectangular area extracted in the head area extracting step 102, pixels having RGB values close to the  
20 average color of the face calculated in the first step in a specified range are recorded as skin-color pixels. Next, the skin-color pixels thus recorded are analyzed to determine the face outline.

The above-mentioned image generation calculating  
25 method from the picked-up image is realized by an image

generation program, and the program is recorded in a recording medium that can be read by a computer, etc., and supplied.

The first embodiment has exemplified the case in which,  
5 in the head area extracting section 2, in order to obtain a differential image by using two time-wise consecutive images among input images picked up the image input section 1, the absolute value of the difference of the corresponding pixels is binarized. However, a method other than this,  
10 for example, a method in which an image is subjected to a process for extracting the outline of a person, such as an edge analysis, so as to extract the outline including the head and shoulder as described in the first embodiment, may be used, and thereafter, in the same manner as described  
15 above, a person's portrait may be generated.

Moreover, the first embodiment has exemplified the case in which, in the head area extracting section 2, a differential image is calculated by using two time-wise consecutive images among input images picked up the image  
20 input section 1. However, for example, an image corresponding to one frame picked up by the image input section 1 is used, and supposing that only one person is included in the image and that the background has a uniform color, a new image is formed by shifting this image up and  
25 down or right and left by several pixels, and to these two

images, the same process as the differential image process of the head area extracting section 2 described in the first embodiment may be applied; thus, it is possible to obtain the same results.

5       As described above, in the first embodiment, based upon two-dimensional images picked up by the image input section 1, a characteristic feature from the person's face is detected by analyzing the luminance of pixel values, and the person's portrait, etc., that is colored based upon the  
10       calculated average color in the vicinity of the characteristic feature is formed, that is, an image emphasizing the characteristic feature of the pickup subject is created. Therefore, without the need of template matching, the characteristic feature of the face parts, etc.  
15       are automatically detected, and the skin color, etc. of the face is calculated from the picked-up image. Consequently, it is not necessary to specify the color beforehand, and with respect to the background, in the case of a virtually stationary background, the pickup subject, such as a person,  
20       can be detected stably independent of the kinds of the background, with the result that an image in which the characteristic feature of the pickup subject are emphasized, such as a person's portrait formed by the results of picked-up images, can be generated in a stable manner.

25       A second embodiment of the present invention will be

explained next. The arrangement of a person's portrait generation device in accordance with the second embodiment is the same as that of the first embodiment. In the second embodiment, in addition to the functions explained in the first embodiment, in the image processing section 5, the results of the detection of each of the face parts positions, such as the eyes, the mouth, etc., made by the feature detection section 3 are utilized so as to deform the person's portrait derived from a face image, thereby forming a deformed face image representing emotional changes, such as a smiling face and a crying face.

Fig. 14A to Fig. 14F are examples that show such deformations of a person's portrait. By utilizing a portrait shown in Fig. 14A (which is the same as the portrait shown in Fig. 7), the person's portrait is deformed based upon the positions of the eyes and mouth, thereby obtaining the results shown in Fig. 14B to Fig. 14F. These are examples of the person's portrait deformations. Fig. 14B shows a smiling face, Fig. 14C shows a crying face, Fig. 14D shows an angry face, Fig. 14E shows a fat face, and Fig. 14F thin face.

Next, an explanation will be given of specific sequences of the face deformations. First, the face deformations shown in Fig. 14B to Fig. 14D are obtained by deforming a person's portrait image in accordance with

directions of arrows determined based upon the positions of the eyes and the position of the mouth shown in Fig. 14G to Fig. 14I respectively. Moreover, the face deformations shown in Fig. 14E and Fig. 14F are obtained by deforming  
5 the person's portrait image so as to expand and shrink in the directions of arrows determined based upon the jaw line, as shown in Fig. 14J to Fig. 14K.

As described above, a person's portrait is generated based upon an input image, and it is deformed based upon  
10 the detection positions of the face parts, thereby forming the person's portraits representing emotional changes such as a crying face and a smiling face; thus, it becomes possible to automatically generate such images without the necessity of template selection by the user.

15 Next, Fig. 13 is a flow chart showing steps in the image processing step 105.

First, based upon an input image within the face outline calculated by the face outline determining step 104, a person's portrait corresponding to Fig. 7 is generated.  
20 Next, after discriminations have been made as to whether or not an insertion of any of the face parts is required or whether or not a deformation of any of the face parts is required, a desired person's portrait image is obtained.

The above-mentioned image generation calculating  
25 method from the picked-up image is realized by an image

generation program, and the program is recorded in a recording medium that can be read by a computer, etc., and supplied.

In the second embodiment, the explanation has been given of the deformations of a person's portrait image by the use of deformations of the face parts. However, for example, the face parts from an original image may be used, and the original image may be partially deformed based upon the detection positions of the face parts so as to provide face deformations representing various emotions. Moreover, in the second embodiment, the explanation has been given of the case in which the deformations are made based upon the positions of the eyes and the position of the mouth. However, characteristic features other than these, for example, the positions of the nose and the ears, may be used as the references on which the deformations are made. Furthermore, in the second embodiment, with respect to the deforming method for emotional face images, the explanation has been given by reference to Fig. 14G to Fig. 14K. However, the present invention is not intended to be limited by this method, and any known method may of course be used to provide the deformations.

A third embodiment of the present invention will be explained next. The arrangement of a person's portrait generation device in accordance with the third embodiment

is the same as that of the first embodiment. In the third embodiment, in addition to the functions explained in the first embodiment, in the image processing section 5, other face parts are put at the face parts positions, such as the eyes, the mouth, etc., detected by the feature detection section 3, in a replacing manner, so as to form another face image different from the person's portrait image shown in the first embodiment.

Fig. 15A to Fig. 15E are drawings that explain how already prepared desired face parts are inserted to the positions of the eyes and mouth of the person's portrait image shown in Fig. 7 to form another face image. Fig. 15A shows a case in which asterisk marks are inserted at the positions of the eyes and mouth. Further, when the asterisk mark corresponding to the right eye is replaced with an image of a right eye shown in Fig. 15B, the asterisk mark corresponding to the left eye is replaced with an image of a left eye shown in Fig. 15C, and the asterisk mark corresponding to the mouth is replaced with an image of a mouth shown in Fig. 15D, then the portrait shown in Fig. 15E is obtained.

As described above, in a person's portrait generated from an input image, other face parts images are inserted to the face parts positions automatically detected, thereby forming another face image. Thus, it is possible to omit

the user's manually specifying operations related to parts positions, and also to automatically generate various face images by preparing a number of such face parts.

A fourth embodiment of the present invention will be explained next. The fourth embodiment exemplifies a case in which the aforementioned person's portrait generation device or person's portrait generation method is applied to a communication terminal.

Fig. 16 is a drawing that exemplifies a case in which the present invention is applied to a mobile telephone 31 serving as a communication terminal. As shown in Fig. 16A, a face image is picked up by a small-size camera 32 attached to the mobile telephone 31. Then the image is subjected to a face parts position detection and a person's portrait generating process to obtain the person's portrait shown in Fig. 16B. This portrait (data of the portrait) may be then transmitted to a desired destination. On the other hand, the portrait shown in Fig. 16B may be deformed as shown in Fig. 16C. The portrait may be deformed to express person's emotions such as cry, smile, anger and joy, or expressing a fat face or a thin face, thereby making it possible to transmit the resulting person's portrait data. Moreover, face parts position information may be detected from the portrait shown in Fig. 16B, and the face parts may be exchanged with other parts or symbols as shown in Fig. 16D. The



portraits shown in Fig. 16C or Fig. 16D may be transmitted to desired destination.

The following description will propose examples of methods for actually using these person's portraits that are effectively used at the time of communication, such as mail exchange. For example, a setting may be made in which, on a waiting screen at the time of mail receiving, the user's portrait is displayed with changes in emotions, such as crying or smiling, depending on the senders; thus, it is possible to immediately judge who sent a mail or what kind of person sent a mail.

In another example of the application, mail senders' portraits are preliminarily registered, and a setting is made so that, upon receipt of a mail, the corresponding sender's portrait is displayed; thus, it is possible to immediately judge who sent the mail. Moreover, even when the receiver is not an acquaintance, sending the sender's portrait may make it possible to provide a friendly mood.

Furthermore, mail subjects may include items such as "sad information" and "good information", and a deformed person's portrait expressing a crying state, smiling state, etc. is provided on the receiver's side; thus, it becomes possible to immediately judge the contents of the mail by the expression of the portrait.

Here, the person's portrait formed by the present

invention may be utilized as various indicators for mobile communication apparatuses, etc. For example, a setting may be made so that, when the battery is running out, the user's thin portrait is displayed; thus, it is possible to easily  
5 know the exchanging time or charging time for the battery. Moreover, when unread received mails have been accumulated, the receiver's fat face may be displayed so that it is possible to easily know the degree of accumulated mails. Furthermore, when direct sun light enters the screen, a dazzled face may  
10 be displayed thereon so that the corresponding information is easily given.

With respect to other different applications, when a game, etc., is played, upon achievement of a high mark, a smiling face may be displayed while upon receipt of a low  
15 mark, a crying face may be displayed; thus, the game becomes more enjoyable. Moreover, the receiver's portrait may be combined with a transmitted person's portrait to have fun. Furthermore, parts such as beard, wigs, etc. may be preliminarily prepared, and these may be combined with a  
20 person's portrait to have fun. Furthermore, an angry face may be colored in red, or tear parts, preliminarily prepared separately, may be added to a crying face to have fun.

The above-mentioned communication terminal is not intended to be limited to the mobile telephone, and any  
25 communication terminal may be used as long as it can transmit

and receive person's portrait images. For example, it can be applied to PDAs (Personal Digital Assistant), notebook PCs, television telephones.

Moreover, in accordance with the person's portrait generation device of the present invention, person's portraits may be attached to electric mails, etc. used in mobile telephones and personal computers. Alternatively in a video conference, etc., using cameras between remote places, instead of showing real images of the participants' faces, the participants' portrait images automatically generated may be given on the screen, and in response to audio data in the discussion, the mouth portions of the portraits may be moved; thus, the participants are allowed to have realistic feelings, while avoiding a feeling of oppression the users might have due to the appearance of their actual face on the screen.

Since the present invention is arranged and has sequences as described above, it provides the following effects:

The person's portrait generation device in accordance with the present invention is provided with the image input section, the head area extracting section, the feature detection section, the face outline determining section and the image processing section; therefore, without the need of template matching, the characteristic features of the

face parts, etc. are automatically detected and the skin color, etc. of the face is calculated from the picked-up image so that it is not necessary to specify the color beforehand. Moreover, with respect to the background, in  
5 the case of a virtually stationary background, the pickup subject, such as a person, can be detected stably independent of the kinds of the background, with the result that an image in which the characteristic features of the pickup subject are emphasized, such as a person's portrait formed by the  
10 results of picked-up images, can be generated in a stable manner.

Moreover, the communication terminal of the present invention is provided with the image input section, the head area extracting section, the feature detection section, the  
15 face outline determining section and the image processing section, and the person's portrait thus formed is transmitted and received through the communication unit; therefore, without the need of template matching, the characteristic features of the face parts, etc. are automatically detected  
20 and the skin color, etc. of the face is calculated from the picked-up image so that it is not necessary to specify the color beforehand. Moreover, with respect to the background, in the case of a virtually stationary background, the pickup subject, such as a person, can be detected stably independent  
25 of the kinds of the background, with the result that an image

in which the characteristic features of the pickup subject are emphasized, such as a person's portrait formed by the results of picked-up images, can be generated in a stable manner, and the person's portrait thus formed is utilized  
5 so as to inform the user of the transmission and receipt and is also utilized as an indicator for the communication terminal so that it becomes possible to carry out pleasant communications while having fun.

The person's portrait generation method of the present  
10 invention is provided with the image input step, the head area extracting step, the feature detection sequence, the face outline determining sequence and the image processing sequence; therefore, without the need of template matching, the characteristic features of the face parts, etc. are  
15 automatically detected and the skin color, etc. of the face is calculated from the picked-up image so that it is not necessary to specify the color beforehand. Moreover, with respect to the background, in the case of a virtually stationary background, the pickup subject, such as a person,  
20 can be detected stably independent of the kinds of the background, with the result that an image in which the characteristic features of the pickup subject are emphasized, such as a person's portrait formed by the results of picked-up images, can be generated in a stable manner.

25 Moreover, the communication method of the present

invention is provided with the image input step, the head  
area extracting step, the feature detection step, the face  
outline determining step, the image processing step and the  
step which, upon receipt of information, displays the  
5 person's portrait thus formed so as to inform the user of  
the receipt of the information; therefore, without the need  
of template matching, the characteristic features of the  
face parts, etc. are automatically detected and the skin  
color, etc. of the face is calculated from the picked-up  
10 image so that it is not necessary to specify the color  
beforehand. Moreover, with respect to the background, in  
the case of a virtually stationary background, the pickup  
subject, such as a person, can be detected stably independent  
of the kinds of the background, with the result that an image  
15 in which the characteristic features of the pickup subject  
are emphasized, such as a person's portrait formed by the  
results of picked-up images, can be generated in a stable  
manner, and the person's portrait thus formed is utilized  
so as to inform the user of the transmission and receipt  
20 so that it becomes possible to carry out pleasant  
communications while having fun.

Furthermore, the recording medium of the present  
invention in which the person's portrait generation program  
is recorded is provided with: the head area extracting  
25 program for extracting a head area of a person from a

differential image of a plurality of two-dimensional images  
picked up by an image input section, the feature detection  
program for detecting positions of characteristic features  
of the person's portrait by dividing the head area into face  
5 part areas for respective face parts, finding projection  
data of binarized images for the respective face parts areas  
and detecting the position of each of the face parts based  
upon a center-of-gravity position of the projection data,  
the face outline determining program for determining a border  
10 between a face outline and a background within the head area  
by specifying a skin color area of the two-dimensional image,  
and the image processing program for creating a person's  
portrait in which the characteristics in the person's face  
is emphasized by changing the two-dimensional image with  
15 respect to each of the face parts; therefore, the person's  
portrait thus generated is read by a communication terminal,  
etc. capable of transmitting and receiving images so that  
it is utilized so as to inform the user of the transmission  
and receipt, and is also utilized as an indicator for the  
20 communication terminal.

Although the invention has been described with respect  
to a specific embodiment for a complete and clear disclosure,  
the appended claims are not to be thus limited but are to  
be construed as embodying all modifications and alternative  
25 constructions that may occur to one skilled in the art which

fairly fall within the basic teaching herein set forth.